



DESCRIPTION

PLASTIC INJECTION MOLDED ADJUSTMENT RING
 MOLDED FROM HIGH DENSITY POLYETHYLENE AS DEFINED IN ASTM SPECIFICATION D4976

ACTUAL RESIN PROPERTIES WILL VARY ALLOWING FOR THE UTILIZATION OF A MAXIMUM PERCENT OF RECYCLED MATERIAL

THE PERCENT OF POST CONSUMER WASTE TO INDUSTRIAL WASTE WILL VARY WITH AVAILABILITY AND PROPERTY RETENTION NEEDS

COLOR, SHADE AND UNIFORMITY WILL VARY WITH THE MIX OF THE POST CONSUMER AND INDUSTRIAL WASTE MATERIALS

DIMENSIONS SHOWN ARE NOMINAL - ACTUAL SIZE WILL VARY WITHIN ALLOWABLE TOLERANCE AND REQUIRED FIT

DIMENSION SCHEDULE

CONE SIZE	DIM A	DIM B	DIM C	DIM D	DIM H1	H2
24	33.50	23.75	5.00	23.25	.75	1.50
27	36.50	26.75	5.00	26.25	.75	1.50
30	39.50	29.75	5.00	29.25	1.50	2.25
32	41.50	31.75	5.00	31.25	1.25	2.25
34	41.50	33.75	4.00	33.25	1.25	2.25
36	47.5	35.75	5.5	35.25	1.5	2.5

APPROVAL DATE _____ BY _____	DESCRIPTION POLYETHYLENE MANHOLE ADJUSTMENT RING SLOPE DESIGN	SPECIFICATION REFERENCE	STANDARD PLATE NO.
-------------------------------------	---	-------------------------	--------------------