

## PRESS-SEAL CORPORATION

P.O. Box 10482 - Fort Wayne, IN 46852 2424 West State Blvd. - Fort Wayne, IN 46808 Toll Free: 800-348-7325 Office: 260-436-0521 sales@press-seal.com www.press-seal.com

Printing Date 07/16/2015 Revision Date 02/23/2015 Safety Data Sheet acc. to OSHA HCS Revision Number 2

## 1 Identification

- · Product identifier
- · Trade name: EZ-Stik 3 Trowelable Sealant
- · Article number: 730825-1
- · Relevant identified uses of the substance or mixture. Sealant
- · Application of the substance / the mixture Sealant
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Royal Adhesives & Sealants, LLC 4401 Page Avenue. P. O. Box 457 Michigan Center, MI 49254

Information Phone Number: 517-764-0334

- · Information department: Environment protection department.
- · Emergency telephone number:

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Sol. 1 H228 Flammable solid.



GHS08 Health hazard

Carc. 1B H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard statements Flammable solid.

(Contd. on page 2)

Printing Date 07/16/2015 Revision Number 2 Revision Date 02/23/2015

Trade name: EZ-Stik 3 Trowelable Sealant

(Contd. of page 1)

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Additional information:
- 3.8 percent of the mixture consists of ingredient(s) of unknown toxicity.
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Hazardous components: |                                                 |         |
|-------------------------|-------------------------------------------------|---------|
| 64742-89-8              | Solvent naphtha (petroleum), light aliph.(VM&P) | 25-50%  |
| 1332-58-7               | Kaolin                                          | 25-50%  |
| 14807-96-6              | Talc (Mg3H2(SiO3)4)                             | 2.5-10% |

#### · Additional information:

It is highly unlikely the powders and pigments compounded within this product would pose a hazardous risk from inhalation as they are no longer a respirable particulate. Exposure to these ingredients as used in sealants, putties, bedding compounds and other non-sprayable products is highly unlikely. The concentrations listed in the (Contd. on page 3)

Printing Date 07/16/2015 Revision Number 2 Revision Date 02/23/2015

Trade name: EZ-Stik 3 Trowelable Sealant

(Contd. of page 2)

composition section are percent by weight unless a gas. Gas concentrations are expressed in percent by volume.

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Overexposure, remove to fresh air and seek medical attention.
- · After skin contact:

Wipe excess from skin.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Protective clothing and respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special measures required.
- · Information about protection against explosions and fires: Keep container closed when not in use.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- · Information about storage in one common storage facility: Keep away from open flames and high temperatures.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)

Printing Date 07/16/2015 Revision Number 2 Revision Date 02/23/2015

Trade name: EZ-Stik 3 Trowelable Sealant

· Specific end use(s) No further relevant information available.

(Contd. of page 3)

### 8 Exposure controls/personal protection

· Control parameters

| quire monitoring at the workplace: | · Comp                          |
|------------------------------------|---------------------------------|
|                                    | 1332-                           |
| 3                                  | PEL                             |
| <i>3</i>                           | REL                             |
|                                    | TLV                             |
|                                    | 14807                           |
|                                    | PEL                             |
|                                    | REL                             |
| 3<br>3<br>3                        | 1332- PEL REL TLV 14802 PEL REL |

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

TLV Long-term value: 2\* mg/m³
\*as respirable fraction; E

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Protective gloves.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses with side shields.



Tightly sealed goggles

(Contd. on page 5)

Printing Date 07/16/2015 Revision Number 2 Revision Date 02/23/2015

Trade name: EZ-Stik 3 Trowelable Sealant

· Body protection: Protective work clothing

(Contd. of page 4)

| Physical and chemical prope         | · · · · · · · · · · · · · · · · · · ·                                                      |
|-------------------------------------|--------------------------------------------------------------------------------------------|
| Information on basic physical and   | chemical properties                                                                        |
| General Information                 |                                                                                            |
| Appearance: Form:                   | Pasty Solid                                                                                |
| r orm:<br>Color:                    | Fusty Sotta<br>Black                                                                       |
| Odor:                               | Naptha                                                                                     |
| Odour threshold:                    | Not determined.                                                                            |
| pH-value:                           | Not determined.                                                                            |
| Change in condition                 |                                                                                            |
| Melting point:                      | Undetermined.                                                                              |
| Boiling point:<br>Flash point:      | 8.9 °C (48 °F)                                                                             |
| Ignition temperature:               |                                                                                            |
| Decomposition temperature:          | Not determined.                                                                            |
| Auto igniting:                      | Product is not selfigniting.                                                               |
| Danger of explosion:                | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| Flammable limits:                   |                                                                                            |
| Lower:                              | Not Available                                                                              |
| Upper:                              | Not Available                                                                              |
| Vapor pressure:                     | Not determined.                                                                            |
| Specific gravity:                   | 1.16                                                                                       |
| Relative density                    | Not determined.                                                                            |
| Vapour density                      | Not determined.                                                                            |
| Evaporation rate                    | 0.12                                                                                       |
| Solubility in / Miscibility with    |                                                                                            |
| Water:                              | Not soluble                                                                                |
| Partition coefficient (n-octanol/wa | ter): Not determined.                                                                      |
| Viscosity:                          |                                                                                            |
| Dynamic:                            | Not determined.                                                                            |
| Kinematic:                          | >20.5 cSt                                                                                  |
| Solvent content:                    |                                                                                            |
| Organic solvents:                   | 25 %                                                                                       |
| Solids content:                     | 75 %                                                                                       |
| Other information                   | VOC content - 330 g/L                                                                      |

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

Printing Date 07/16/2015 Revision Number 2 Revision Date 02/23/2015

Trade name: EZ-Stik 3 Trowelable Sealant

(Contd. of page 5)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, flames, sparks.
- · Incompatible materials: Reacts with strong oxidizing agents.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: May irritate the skin.
- · on the eye: May irritate the eye.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1333-86-4 Carbon black

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Small amounts can be disposed of with household waste after the product has cured or skinned over. Larger quantities should be disposed of according to state and local regulation.

(Contd. on page 7)

Printing Date 07/16/2015 Revision Number 2 Revision Date 02/23/2015

Trade name: EZ-Stik 3 Trowelable Sealant

(Contd. of page 6)

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

| 1 4 70     |            | C         | . •  |
|------------|------------|-----------|------|
| 14 Trans   | nort in    | torma     | TON  |
| IT II WILL | יווי יווטע | UI IIIIII | uuuu |

· UN-Number

· DOT, ADR, IMDG, IATA UN1325

· UN proper shipping name

DOT Flammable solids, organic, n.o.s.
 ADR 1325 Flammable solids, organic, n.o.s.
 ⋅ IMDG, IATA FLAMMABLE SOLID, ORGANIC, N.O.S.

· Transport hazard class(es)

 $\cdot DOT$ 



• Class 4.1 Flammable solids, self-reactive substances and solid desensitised explosives

· ADR, IMDG, IATA



• Class 4.1 Flammable solids, self-reactive substances and solid desensitised explosives

· Packing group

· DOT, ADR, IMDG, IATA

· Environmental hazards: Not applicable.

• Special precautions for user Warning: Flammable solids, self-reactive substances and solid

desensitised explosives

 $\cdot$  EMS Number: F-G,S-G

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": UN1325, Flammable solids, organic, n.o.s., 4.1, II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

(Contd. on page 8)

Printing Date 07/16/2015 Revision Number 2 Revision Date 02/23/2015

Trade name: EZ-Stik 3 Trowelable Sealant

(Contd. of page 7)

#### · TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- · Chemicals known to cause cancer:

64742-89-8 | Solvent naphtha (petroleum), light aliph.(VM&P)

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

#### · (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

None of the ingredients is listed.

| · TLV (Threshold Limit Value established by ACGIH) |                     |    |
|----------------------------------------------------|---------------------|----|
| 1332-58-7                                          | Kaolin              | A4 |
| 1333-86-4                                          | Carbon black        | A4 |
| 14807-96-6                                         | Talc (Mg3H2(SiO3)4) | A4 |

## · MAK (German Maximum Workplace Concentration)

| 1333-86-4  | Carbon black               | <i>3B</i> |
|------------|----------------------------|-----------|
| 14807-96-6 | <i>Talc</i> (Mg3H2(SiO3)4) | <i>3B</i> |

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Environment protection department.
- · Creation Date: 10/25/2014
- · Date of preparation / last revision 07/16/2015 / 1
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 9)

(Contd. of page 8)

# Safety Data Sheet acc. to OSHA HCS

Printing Date 07/16/2015 Revision Number 2 *Revision Date 02/23/2015* 

Trade name: EZ-Stik 3 Trowelable Sealant

 $Flam.\ Sol.\ 1: Flammable\ solids,\ Hazard\ Category\ 1$ 

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Carc. 1B: Carcinogenicity, Hazard Category 1B