TIRED OF FAILING MANHOLES?

Learn Why Engineers & Contractors are Ditching Concrete and Choosing Ladtech





CORROSION PROOF


- Impervious to Hydrogen Sulfide Gas (H₂S)
- · No Deterioration from Road Salt



ELIMINATE I & I


- · Butyl Rubber Sealant Eliminates Infiltration
- · Completely Watertight

UV RESISTANT



EASY INSTALLATION

- Lightweight Grade Rings
- · Slope Rings Allow Easy Adjustment to Any Grade
- Rings as Thin as 1/4" for Precision Fit
- · Easily Specifiable



DURABILITY

- · Built for Heavy Traffic H25 Traffic Rated
- 100-Year Life Expectancy



ENVIRONMENTALLY FRIENDLY

- Made from 100% Recycled HDPE
- Made in the USA



SPECIFY THE LADTECH SYSTEM High Density Polyethylene Manhole Adjusting Rings

REQUEST A FREE DEMO www.ladtech.com 877.ADJ.RING (235-7464)



SPECIFY THE LADTECH SYSTEM

High Density Polyethylene Manhole Adjusting Rings



ROUND RINGS

Available In:

24" and 27" with Adjustments of 1.25", 1.5", 2", 4" and .75" to 1.5" Slope 30" with Adjustments of 1.5", 2.25", 4" and 1.5" to 2.25" Slope 32" with Adjustments of 2", 3", 3" fiberglass and 1.25" to 2.25" Slope 34" with Adjustments of 2", 3" and 1.25" to 2.25" Slope 36" with Adjustment of 1.25", 2.25", 3.00" and 2.50" to 1.50" Slope



24" x 24" with Flat Adjustments of 1.25", 1.5", 2", 2.75" 24" x 24" with Slope Adjustments of .75" to 1.5", 1.25" to 2.75" and 2" to 2.75"



RECTANGLE RINGS

Available In:

2436F150 - 24" X 36" X 1.50" 2436F200 - 24" X 36" X 2.00" 2436F275 - 24" X 36" X 2.75"

2436SX275 - 24" X 36" / 2.75" X 1.25" SIDE / SIDE (3' leg) Slope 24S36X275 - 24" X 36" X 2.75" X 1.25" FRONT / BACK (2' leg) Slope 2436SX175 - 24" X 36" / 1.75" X 1.25" (3' leg) Slope



SPACER RINGS

Available In:

24" X .25" Round 27" X .25" Round 30" X .25" Round

32" X .25" Round

34" X .25" Round 36" X .25" Round 24" X 24" X .25" Square 24" X 36" X .25" Rectangular



CON-SEAL BUTYL SEALANT

Available In: CS-102 - .5" x 21' CS-202 - 5" x 21' 12 Rolls per Carton